KEFO® SINCE 1949

LLG® LABWARE

LABORHITS

LLG-uni*TOPDISPENS* 2 & 2 Duo

High chemical compatibility

Adjustable dispensing angle flexible

Piston made of PTFE & re-circulation valve

LLG-uni*TOPDISPENS* 2

WARRANTY 3 YEARS

LLG-uni*TOPDISPENS* Duo 2

- **Refilling and rinsing** without the need to dismount
- **4 modes of dispensing: Dilution, Rinsing, Dual Liquid Handling and Re-circulation** in a single unit

KEFO d.o.o.
Slovenija | Brnčičeva 29, 1231 Ljubljana-Črnuče | www.kefo.si
BiH | Ćorovićeva 1A, 71123 I.Sarajevo | www.kefo.ba
Srbija | Bačka 1U, 11 080 Zemun | www.kefo.rs
Hrvatska | N. Tesle 10, 44000 Sisak | www.kefo.hr

KEFO SINCE 1949

LLG LABWARE

LABORHITS

LLG-uni*TOPDISPENS* 2 & 2 Duo

- Springless PTFE valve, PTFE piston with chemically resistant ETP O-ring enables high chemical compatibility
- Glass cylinder from borosilicate glass 3.3
- Re-circulation valve enables easy priming and bubble free dispensing
- Smooth, reproducible and effortless dispensing
- 360° rotation possible due to specially designed bottle adapter
- Flexible and adjustable delivery nozzle provides dispensing angle flexibility to the user
- Specially designed volume adjustment knob for quick and easy volume setting
- The telescopic extractable intake tube can be easily adjusted to varying bottle heights
- Nozzle cap reduces contact with air and prevents drying and dripping if the tip cover is attached
- Five bottle adaptors included (28 mm, 32 mm, 37 mm, 40 mm and 45 mm). Standard thread: 30 mm.
- Fully autoclavable at 121 °C, 15 psi for 10 to 15 min
- Individually calibrated in accordance with ISO 8655 standards and each unit is supplied with an individual calibration certificate
- Accuracy max. vol. (≤ ± R%): 0.6
- Precision max. vol. (≤ CV%): 0.2

LLG-uni*TOPDISPENS* 2

Volume ml	Graduations ml	PK	Cat. No.
0.25 - 2.5	0.05	1	**6.282 275**
0.5 - 5	0.1	1	**6.282 276**
1 - 10	0.2	1	**6.282 277**
2.5 - 30	0.5	1	**6.282 278**
5 - 60	1.0	1	**6.282 279**
10 - 100	2.0	1	**6.282 280**

LLG-uni*TOPDISPENS* 2 Duo

Volume ml	Graduations ml	PK	Cat. No.
0.25 - 2.5	0.05	1	**6.282 281**
0.5 - 5	0.1	1	**6.282 282**
1 - 10	0.2	1	**6.282 283**
2.5 - 30	0.5	1	**6.282 284**
5 - 60	1.0	1	**6.282 285**
10 - 100	2.0	1	**6.282 286**

KEFO d.o.o.
Slovenija | Brnčičeva 29, 1231 Ljubljana-Črnuče | www.kefo.si
BiH | Ćorovićeva 1A, 71123 I.Sarajevo | www.kefo.ba
Srbija | Bačka 1U, 11 080 Zemun | www.kefo.rs
Hrvatska | N. Tesle 10, 44000 Sisak | www.kefo.hr